

SAFETY DATA SHEET



F190L H2OProf, Liquid

Date Prepared : 05/18/2015

SDS No : SCC-F190L

Date Revised : 09/14/2016

Revision No : 1

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: F190L H2OProf, Liquid
PRODUCT DESCRIPTION: H2OProf, Liquid
PRODUCT CODE: F190L
PRODUCT FORMULATION NAME: F190L H2OProf, Liquid
CHEMICAL FAMILY: Water Base Alkaline Emulsion

MANUFACTURER

Sauereisen
 160 Gamma Drive
 Pittsburgh, PA 15238
Emergency Contact: John Kozak
Emergency Phone: (800)424-9300
Alternate Contact: Don Schubert
Customer Service: 412 963-0303
E-Mail: jakozak@sauereisen.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical):1-800-222-1222
 CHEMTREC (US Transportation): 1-800-424-9300
 CHEMTREC (Outside US):1-703-527-3887

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Respiratory Tract Irritation, Category 3
 Skin Irritation, Category 2
 Eye Irritation, Category 2B

GHS LABEL

Exclamation
 mark

SIGNAL WORD: WARNING**HAZARD STATEMENTS**

H320: Causes eye irritation.
 H315: Causes skin irritation.
 H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS**Prevention:**

P264: Wash ... thoroughly after handling.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water/...
 P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/national regulations.

POTENTIAL HEALTH EFFECTS

EYES: Contact causes eye irritation.

SKIN: Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

INHALATION: Causes sneezing and burning or itching in nose and throat.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%
Complex Alkaline Earth Silicates	100

4. FIRST AID MEASURES

EYES: Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

SKIN: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

INGESTION: If Swallowed, do not induce vomiting. Immediately drink two large glasses of water or activated charcoal slurry. Seek Medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Not expected to be a problem.

ADDITIONAL INFORMATION: Note: To prepare activated charcoal slurry, add 50 grams of activated charcoal to 400 ml of water and mix well.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: NA = Not Applicable

EXPLOSION HAZARDS: NA = Not Applicable

FIRE FIGHTING PROCEDURES: NA = Not Applicable

FIRE EXPLOSION: NA = Not Applicable

SENSITIVE TO STATIC DISCHARGE: None

SENSITIVITY TO IMPACT: None

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

LARGE SPILL: For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing.

For Industrial Use only!

Do not take internally.
 May cause irritation.
 Wear chemical splash goggles, gloves and protective clothing.
 Wash thoroughly after handling.

STORAGE: Store in a cool, dry place.
 Keep container closed when not in use.
 Keep away from food and drinking water.
 Always mix well before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)			
Chemical Name	EXPOSURE LIMITS		
	Type		
Complex Alkaline Earth Silicates	OSHA PEL	TWA	ppm
	ACGIH TLV	TWA	mg/m ³

ENGINEERING CONTROLS: Normal ventilation for good working conditions should be used.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical resistant goggles and/or face shield.

SKIN: Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved workclothes. Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

RESPIRATORY: Use NIOSH approved mist respirator where spray occurs. For emergencies, a self contained breathing apparatus or a full-face respirator is recommended. If TLV of any component is exceeded, use appropriate respiratory protection or ventilate in accordance with OSHA Regulation 29 CFR 1910.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: No appreciable odor.

ODOR THRESHOLD: NA = Not Applicable

APPEARANCE: Viscous liquid

COLOR: White

pH: 13.5

PERCENT VOLATILE: NA = Not Applicable

FLASH POINT AND METHOD: NA = Not Applicable

FLAMMABLE LIMITS: NE to NE

VAPOR PRESSURE: Vapor is water

VAPOR DENSITY: Same as water vapor.

BOILING POINT: (212°F)

FREEZING POINT: (32°F)

MELTING POINT: (32°F)

SOLUBILITY IN WATER: Soluble

EVAPORATION RATE: < 1

SPECIFIC GRAVITY: 1.14

(VOC): 45

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under normal conditions of use and storage.

CONDITIONS TO AVOID: Flammable hydrogen gas may be produced on prolonged contact with metals such as Aluminum, tin, lead, and zinc.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

INCOMPATIBLE MATERIALS: Materials to avoid: Acids, salts, or alcohols may cause gel formation (non-hazardous).

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

DERMAL LD₅₀: No data available.

ORAL LD₅₀: No data available.

INHALATION LC₅₀: No data available.

SERIOUS EYE DAMAGE/IRRITATION: Eye, Skin and Inhalation Irritant.

CARCINOGENICITY

NOTES: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union)

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY (ACUTE): Sodium Silicate has low toxicity. TLM 96 hr in mosquitofish is 2,320 mg/L. High pH (alkalinity) of undiluted material is harmful to aquatic life.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

EMPTY CONTAINER: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Caustic Alkali Liquid, N.O.S. (Copolymer Silicate)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN 1719

PACKING GROUP: III

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7/8: Keep container tightly closed and dry.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Irritant.

313 REPORTABLE INGREDIENTS: There are no listed chemicals above detection limits in this compound.

TITLE III NOTES: None above detection limits.

CALIFORNIA PROPOSITION 65: Known to the State of California to cause cancer and reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7/8: Keep container tightly closed and dry.

WHMIS CLASS: Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

DOMESTIC SUBSTANCE LIST (INVENTORY): Components included on inventory

16. OTHER INFORMATION

PREPARED BY: John A Kozak **Date Revised:** 09/14/2016

REVISION SUMMARY: This SDS replaces the 05/18/2015 SDS. Revised: **Section 14:** DOT (DEPARTMENT OF TRANSPORTATION) (TECHNICAL NAME, PRIMARY HAZARD CLASS/DIVISION, UN/NA NUMBER, PACKING GROUP). **Section 16:** HMIS RATING (PERSONAL PROTECTION).

HMIS RATING

HEALTH	<input type="checkbox"/>	D
FLAMMABILITY	<input type="checkbox"/>	0
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	D