

SAFETY DATA SHEET



3 TempSeal Cement, Paste

Date Issued : 05/07/2015

SDS No : SCC-003

Date Revised : 06/17/2020

Revision No : 2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3 TempSeal Cement, Paste**PRODUCT DESCRIPTION:** Tempseal Cement, Paste**PRODUCT CODE:** 3**PRODUCT FORMULATION NAME:** 3 TempSeal Cement, Paste**CHEMICAL FAMILY:** Lithium Silicate Cement**MANUFACTURER**

Sauereisen

160 Gamma Drive

Pittsburgh, PA 15238

Emergency Contact: John Kozak**Emergency Phone:** (800)444-8235**Alternate Contact:** Anthony Comport**Customer Service:** 412 963-0303**E-Mail:** jakozak@sauereisen.com**24 HR. EMERGENCY TELEPHONE NUMBERS**

Poison Control Center (Medical):1-800-222-1222

CHEMTREC (US Transportation): 1-800-424-9300

CHEMTREC (Canada Transportation):1-703-527-3887

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Respiratory Tract Irritation, Category 3

Skin Irritation, Category 2

Eye Irritation, Category 2B

GHS LABELExclamation
mark**SIGNAL WORD:** WARNING**HAZARD STATEMENTS**

H320: Causes eye irritation.

H315: Causes skin irritation.

H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS**Prevention:**

P264: Wash ... thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water/...

P322: Specific measures (see ... on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container to ...

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Lithium Polysilicate	< 40	12627-14-4
Aluminum Oxide	< 80	1344-28-1

4. FIRST AID MEASURES

EYES: Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

SKIN: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

INGESTION: If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION: If difficulty breathing, move to fresh air once. Apply artificial respiration if breathing has stopped. Seek medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes pain, redness and tearing.

SKIN: Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Material is non-flammable.

EXTINGUISHING MEDIA: NA = Not Applicable

HAZARDOUS COMBUSTION PRODUCTS: NA = Not Applicable

EXPLOSION HAZARDS: Dusts and aerosols at sufficient concentrations may exhibit explosive characteristics if ignited by static discharge or spark. Exercise care during dusting or misting operations such as grinding or drilling.

FIRE FIGHTING PROCEDURES: NA = Not Applicable

FIRE FIGHTING EQUIPMENT: NA = Not Applicable

FIRE EXPLOSION: NA = Not Applicable

SENSITIVE TO STATIC DISCHARGE: None

SENSITIVITY TO IMPACT: None

HAZARDOUS DECOMPOSITION PRODUCTS: None

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

LARGE SPILL: For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing.

For Industrial Use only!

Do not take internally.

May cause irritation.

Wear chemical splash goggles, gloves and protective clothing.

Wash thoroughly after handling.

STORAGE: Store in a cool, dry place.

Keep container closed when not in use.

Keep away from food and drinking water.

Always mix well before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)			
	EXPOSURE LIMITS		
Chemical Name	Type	ppm	mg/m ³
Aluminum Oxide	ACGIH TLV	STEL	10

ENGINEERING CONTROLS: Normal ventilation for good working conditions should be used.**PERSONAL PROTECTIVE EQUIPMENT****EYES AND FACE:** Safety glasses with side shields, chemical resistant goggles, or face shield. Contact lenses should not be worn.**SKIN:** Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved workclothes. Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.**RESPIRATORY:** No special requirements under ordinary conditions of use and with adequate ventilation.**WORK HYGIENIC PRACTICES:** Wash thoroughly after handling. Safety shower and eyewash station should be within direct access. Keep containers closed.**9. PHYSICAL AND CHEMICAL PROPERTIES****ODOR:** No appreciable odor.**APPEARANCE:** Creamy paste.**COLOR:** White**pH:** ~ 11**PERCENT VOLATILE:** NA = Not Applicable**FLASH POINT AND METHOD:** NA = Not Applicable**FLAMMABLE LIMITS:** NA to NA**AUTOIGNITION TEMPERATURE:** NA = Not Applicable**VAPOR PRESSURE:** Vapor is water**VAPOR DENSITY:** Same as water vapor.**BOILING POINT:** to (212°F)**SPECIFIC GRAVITY:** 2.01**10. STABILITY AND REACTIVITY****REACTIVITY:** Yes**HAZARDOUS POLYMERIZATION:** No**STABILITY:** Stable under normal conditions of use and storage.**CONDITIONS TO AVOID:** None**HAZARDOUS DECOMPOSITION PRODUCTS:** None

INCOMPATIBLE MATERIALS: None

11. TOXICOLOGICAL INFORMATION

SERIOUS EYE DAMAGE/IRRITATION: Eye, Skin and Inhalation Irritant.

GERM CELL MUTAGENICITY: No Data Available

REPRODUCTIVE TOXICITY: No Data Available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available. Contact Env. Dept.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

EMPTY CONTAINER: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated

PRIMARY HAZARD CLASS/DIVISION: Not Regulated

UN/NA NUMBER: NA

PACKING GROUP: NA

LABEL: None

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7: Keep container tightly closed.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Irritant.

313 REPORTABLE INGREDIENTS: There are no listed chemicals above detection limits in this compound.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Aluminum Oxide	< 80	1344-28-1

TITLE III NOTES: None above detection limits.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Lithium Polysilicate	12627-14-4
Aluminum Oxide	1344-28-1

CALIFORNIA PROPOSITION 65: Known to the State of California to cause cancer or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the

very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7: Keep container tightly closed.

WHMIS CLASS: Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

DOMESTIC SUBSTANCE LIST (INVENTORY): Components included on inventory

16. OTHER INFORMATION

PREPARED BY: John A Kozak **Date Revised:** 06/17/2020

REVISION SUMMARY: This SDS replaces the 06/15/2020 SDS.

HMIS RATING

HEALTH	*	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		C