

## SAFETY DATA SHEET



Date Issued : 05/12/2015  
 SDS No : SCC-004  
 Date Revised : 08/08/2019  
 Revision No : 1

## 4 Flotemp Cement

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 4 Flotemp Cement  
**PRODUCT DESCRIPTION:** Flotemp Cement  
**PRODUCT CODE:** 4  
**PRODUCT FORMULATION NAME:** 4 Flotemp Cement  
**CHEMICAL FAMILY:** Magnesium Phosphate Cement

**MANUFACTURER**

Sauereisen  
 160 Gamma Drive  
 Pittsburgh, PA 15238

**Emergency Contact:** John Kozak

**Emergency Phone:** (800)444-8235

**Alternate Contact:** Don Schubert

**Customer Service:** 412 963-0303

**E-Mail:** jakozak@sauereisen.com

**24 HR. EMERGENCY TELEPHONE NUMBERS**

Poison Control Center (Medical):1-800-222-1222

CHEMTREC (US Transportation): 1-800-424-9300

CHEMTREC (Canada Transportation):1-703-527-3887

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Carcinogenicity, Category 1B  
 Target Organ Toxicity (Repeated exposure), Category 2  
 Skin Irritation, Category 2  
 Eye Irritation, Category 2B  
 Reproductive Toxicity, Category 2

**GHS LABEL**

Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** DANGER

**HAZARD STATEMENTS**

H315: Causes skin irritation.  
 H320: Causes eye irritation.  
 H333: May be harmful if inhaled.  
 H335: May cause respiratory irritation.  
 H360: May damage fertility or the unborn child (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
 H350: May cause cancer .  
 H373: May cause damage to lungs or kidneys through prolonged or repeated exposure via inhalation.

**PRECAUTIONARY STATEMENTS****Prevention:**

P201: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash ... thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

#### Response:

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P314: Get medical advice/attention if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing.

#### Storage:

P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with local/national regulations.

### POTENTIAL HEALTH EFFECTS

**EYES:** Contact causes eye irritation.

**SKIN:** Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

**INHALATION:** Dust or vapor irritating to eyes and respiratory tract.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Silica, Crystalline	< 45	14808-60-7
zircon (zr(sio4))	< 40	14940-68-2
Magnesium Oxide	< 15	1309-48-4
Boric Acid	< 2	10043-35-3

### 4. FIRST AID MEASURES

**EYES:** Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

**SKIN:** Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

**INGESTION:** If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention immediately. Never give anything by mouth to an unconscious person.

**INHALATION:** If difficulty breathing, move to fresh air once. Apply artificial respiration if breathing has stopped. Seek medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**CHRONIC EFFECTS:** The adverse health effects-- silicosis, lung cancer, autoimmune and chronic kidney diseases, tuberculosis and non-malignant respiratory diseases-- are chronic effects.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** NA = Not Applicable

**EXTINGUISHING MEDIA:** Water, carbon dioxide, dry chemical, and foam.

**EXPLOSION HAZARDS:** Not sensitive to mechanical impact or static discharge

**FIRE FIGHTING PROCEDURES:** Normal precautions are satisfactory.

**FIRE EXPLOSION:** NA = Not Applicable

**SENSITIVE TO STATIC DISCHARGE:** None

**SENSITIVITY TO IMPACT:** None

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Use dustless methods and place in a closeable container for disposal, or flush with water. Observe environmental regulations.

**GENERAL PROCEDURES:** Sweep, scoop or vacuum the discharged material. Respiratory protection should be worn at all times and skin contact should be avoided. Observe environmental regulations.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid contact with eyes, skin, and clothing.

Avoid breathing dust.

For industrial use only!

Harmful if inhaled.

Do not take internally.

May cause irritation.

Wear chemical splash goggles, gloves, and protective clothing.

Use adequate ventilation and employ respiratory protection where dust or fumes may be generated.

Wash thoroughly after handling.

**HANDLING:** Do not breathe dust. Keep airborne dust concentrations below permissible exposure limit (PEL). Do not rely on sight to determine if dust is in the air. Respirable crystalline silica dust may be in the air without a visible dust cloud. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Maintain, clean and fit tested respirators in accordance with OSHA regulations. Maintain and test ventilation and dust collection equipment. Wash or vacuum clothing that has become dusty.

**STORAGE:** Store in a cool, dry place.

Keep container closed when not in use.

Keep away from food and drinking water.

Always mix well before using.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Silica, Crystalline	OSHA PEL	TWA		5
		STEL	0.05	
	ACGIH TLV	TWA		0.025
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL
zircon (zr(sio4))	OSHA PEL	STEL		15
	ACGIH TLV	TWA		10
Magnesium Oxide	OSHA PEL	TWA		15
	ACGIH TLV	TWA		10 l

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses with side shields, chemical resistant goggles, or face shield. Contact lenses should not be worn.

**SKIN:** Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved workclothes.

Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

**RESPIRATORY:** A suitable respirator complying with the most current NIOSH/ANSI/EN requirements should be used. In the

U.S. use dust respirators in compliance with OSHA Standard 1910.134, and in the E.U. use dust respirators in compliance with EN149:2001 FFP2 or FFP3 and rated for at least 10X WEL. . For emergency, a self-contained positive pressure, breathing apparatus or full face respirator is recommended. If TLV of any component is exceeded, use appropriate respiratory protection or ventilate in accordance with OSHA regulation 29 CFR Part 1910.

**OTHER USE PRECAUTIONS:** Provide adequate general and local exhaust ventilation to meet PEL requirements. Provide workers with dust respirators for use in emergency or non-routine situations where dust levels may exceed PEL. A NIOSH approved half face-piece respirator can be used up to 10x PEL. For up to 100x PEL, use a full face-piece respirator with replaceable dust filters. Higher exposures need an approved air-supplied regulator.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** NA = Not Applicable

**ODOR THRESHOLD:** Not Available

**APPEARANCE:** Granular powder

**COLOR:** White to tan.

**pH:** NA = Not Applicable

**PERCENT VOLATILE:** NA = Not Applicable

**FLAMMABLE LIMITS:** 0 to 0

**VAPOR PRESSURE:** NA = Not Applicable

**VAPOR DENSITY:** NA = Not Applicable

**MELTING POINT:** NA = Not Applicable

**EVAPORATION RATE:** NA = Not Applicable

**SPECIFIC GRAVITY:** 1

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** Stable under normal conditions of use and storage.

**CONDITIONS TO AVOID:** None

**HAZARDOUS DECOMPOSITION PRODUCTS:** None

**INCOMPATIBLE MATERIALS:** None

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

**ORAL LD<sub>50</sub>:** No data is available on the product itself.

**Notes:** Components:

Boric Acid: LD50 (rat): 3500 - 4100 mg/kg

### NOTES:

Acute Silicosis can occur with exposure to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

**SERIOUS EYE DAMAGE/IRRITATION:** Eye, Skin and Inhalation Irritant.

### CARCINOGENICITY

**IARC:** Silica is listed as having sufficient evidence to be a carcinogen in humans and in experimental animals, for the carcinogenicity of quartz and cristobalite. The overall IARC evaluation was that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1).

**NTP:** The National Toxicology Program, in it's Ninth Annual report on Carcinogens, classified "silica, crystalline (respirable)" as a known human carcinogen.

**OSHA:** Crystalline Silica (Quartz) is not regulated by the US Occupational Safety and Health Administration as a carcinogen.

**REPRODUCTIVE TOXICITY:** This product contains Boric acid which may damage fertility or harm the unborn child

**STOT-SINGLE EXPOSURE:**

·Nephrotoxicity - Recent studies suggest that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of kidney disorders.

**GENERAL COMMENTS:**

ADDITIONAL INFORMATION: Crystalline Silica (Quartz)

·Silicosis - The major concern is silicosis caused by the inhalation of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute.

·Scleroderma - There is evidence that exposure to respirable crystalline silica or silicosis is associated with incidence of scleroderma of the lungs.

·Tuberculosis - Individuals with silicosis are at risk to develop tuberculosis, if exposed to persons with tuberculosis.

**12. ECOLOGICAL INFORMATION**

**ENVIRONMENTAL DATA:** Crystalline silica (quartz) is not known to be an environmental hazard.

**ECOTOXICOLOGICAL INFORMATION:** Crystalline silica (quartz) is not known to be ecotoxic. There is no data that suggests that crystalline silica (quartz) is toxic to birds, fish, invertebrates, microorganisms or plants.

**AQUATIC TOXICITY (ACUTE):** No data is available on the product itself. Below is for Boric Acid component.

**48-HOUR EC<sub>50</sub>:** 133 mg/L Daphnia Magna

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The packaging and material may be disposed of in landfills; however, material should be covered or wetted to minimize generation of airborne dust.

**PRODUCT DISPOSAL:** Sweep up excess; flush area with large quantities of water. Material may be disposed of in approved landfill according to official regulations.

**EMPTY CONTAINER:** Disposal must be made according to official regulations.

**RCRA/EPA WASTE INFORMATION:** Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR 261 et seq.

**14. TRANSPORT INFORMATION**

**DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Not Regulated

**TECHNICAL NAME:** NA = Not Applicable

**PRIMARY HAZARD CLASS/DIVISION:** NA = Not Applicable

**ROAD AND RAIL (ADR/RID)**

**PROPER SHIPPING NAME:** Not Regulated

**AIR (ICAO/IATA)**

**SHIPPING NAME:** Not Regulated

**VESSEL (IMO/IMDG)**

**SHIPPING NAME:** Not Regulated

**CANADA TRANSPORT OF DANGEROUS GOODS**

**SHIPPING NAME:** Not Regulated

**15. REGULATORY INFORMATION**

**UNITED STATES**

**DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

R36/37/38: Irritating to eyes, respiratory system and skin.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S7/8: Keep container tightly closed and dry.

### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Chronic. Carcinogen. Irritant.

**313 REPORTABLE INGREDIENTS:** There are no listed chemicals above detection limits in this compound.

**TITLE III NOTES:** None above detection limits.

### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** Crystalline silica (Quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Acts (CERCLA), 40 CFR 302

### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Silica, Crystalline	14808-60-7
zircon (zr(sio4))	14940-68-2
Magnesium Oxide	1309-48-4
Boric Acid	10043-35-3

**TSCA STATUS:** Components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

### REGULATIONS

#### STATE REGULATIONS:

Massachusetts Toxic Use Reduction Act- Silica, Crystalline (respirable size, <10microns) is toxic for purposes of the Massachusetts Toxic Use Reduction Act

Pennsylvania Worker and Community Right to Know Act- Quartz is a hazardous substance under the act, but it is not a special hazardous substance or an environmental hazardous substance.

California Inhalation Reference Exposure Level (REL)- California established a chronic REL of 3 ug for silica crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

**CALIFORNIA PROPOSITION 65:** Known to the State of California to cause cancer or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

**RCRA STATUS:** Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40CFR 261 et seq.

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S7/8: Keep container tightly closed and dry.

**WHMIS CLASS:** Class D, Division 2, Subdivision A: Materials cause other toxic effects, very toxic material.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** Components included on inventory

## 16. OTHER INFORMATION

**PREPARED BY:** John A Kozak      **Date Revised:** 08/08/2019

**REVISION SUMMARY:** This SDS replaces the 05/12/2015 SDS. Revised: **Section 9:** (VOC).

### HMIS RATING

<b>HEALTH</b>	*	<b>1</b>
<b>FLAMMABILITY</b>		<b>0</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>E</b>