

## SAFETY DATA SHEET



## 29 Low Expansion Cement, Powder

Date Issued : 05/23/2016

SDS No : SCC-029P

Date Revised : 07/08/2021

Revision No : 6

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 29 Low Expansion Cement, Powder  
**PRODUCT DESCRIPTION:** Low Expansion Cement, Powder  
**PRODUCT CODE:** 29P  
**PRODUCT FORMULATION NAME:** 29 Low Expansion Cement, Powder  
**CHEMICAL FAMILY:** Zircon Cement Filler

**MANUFACTURER**

Sauereisen  
 160 Gamma Drive  
 Pittsburgh, PA 15238

**Emergency Contact:** John Kozak**Emergency Phone:** (800)444-8235**Alternate Contact:** Anthony Comport**Customer Service:** 412 963-0303**E-Mail:** jakozak@sauereisen.com**24 HR. EMERGENCY TELEPHONE NUMBERS**

Poison Control Center (Medical):1-800-222-1222

CHEMTREC (US Transportation): 1-800-424-9300

CHEMTREC (Canada Transportation):1-703-527-3887

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Eye Irritation, Category 2B

Skin Irritation, Category 2

Target Organ Toxicity (Repeated exposure), Category 2

Acute Toxicity (Inhalation), Category 5

**Environmental:**

Acute Hazards to the Aquatic Environment, Category 3

**GHS LABEL**

Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** WARNING**HAZARD STATEMENTS**

H315: Causes skin irritation.

H320: Causes eye irritation.

H333: May be harmful if inhaled.

H402: Harmful to aquatic life.

H373: May cause damage to lungs or kidneys through prolonged or repeated exposure via inhalation.

**PRECAUTIONARY STATEMENTS****Prevention:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P264: Wash ... thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P271: Use only outdoors or in a well-ventilated area.

#### Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P314: Get medical advice/attention if you feel unwell.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

#### Disposal:

P501: Dispose of contents/container in accordance with local/national regulations.

### POTENTIAL HEALTH EFFECTS

**EYES:** Contact may cause eye irritation.

**SKIN:** Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

**INHALATION:** Dust or vapor irritating to eyes and respiratory tract.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
zircon (zr(sio4))	< 80	14940-68-2
Sodium Fluorosilicate	< 30	16893-85-9

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

**SKIN:** Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

**INGESTION:** If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention immediately. Never give anything by mouth to an unconscious person. Advise physician of possible fluoride exposure.

**INHALATION:** If difficulty breathing, move to fresh air once. Apply artificial respiration if breathing has stopped. Seek medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Causes pain, redness and tearing.

**SKIN:** Contact causes skin irritation.

**INHALATION:** Headache, nausea, and irritation to nose and throat. Prolonged or repeated exposure may cause asthma.

**NOTES TO PHYSICIAN:** Further treatment may be necessary. Contact local poison control center. Possible Fluoride exposure.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** NA = Not Applicable

**FLAME PROPAGATION OR BURNING RATE OF SOLIDS:** None

**GENERAL HAZARD:** NA = Not Applicable

**EXTINGUISHING MEDIA:** NA = Not Applicable

**HAZARDOUS COMBUSTION PRODUCTS:** NA = Not Applicable

**EXPLOSION HAZARDS:** Not sensitive to mechanical impact or static discharge

**FIRE FIGHTING PROCEDURES:** NA = Not Applicable

**FIRE FIGHTING EQUIPMENT:** NA = Not Applicable

**FIRE EXPLOSION:** NA = Not Applicable

**SENSITIVE TO STATIC DISCHARGE:** None

**SENSITIVITY TO IMPACT:** None

**HAZARDOUS DECOMPOSITION PRODUCTS:** NA = Not Applicable

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

**LARGE SPILL:** For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

**SPECIAL PROTECTIVE EQUIPMENT:** Wear gloves, rubber boots, and safety glasses.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid contact with eyes, skin, and clothing.

For industrial use only!

Do not take internally.

May cause irritation.

Wash thoroughly after handling.

**HANDLING:** Wear protective safety glasses, gloves and protective clothing.

**STORAGE:** Store in a cool, dry place.

Keep container closed when not in use.

Keep away from food and drinking water.

Always mix well before using.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m <sup>3</sup>
zircon (zr(sio4))	OSHA PEL	STEL		15
	ACGIH TLV	TWA		10
Sodium Fluorosilicate	OSHA PEL	STEL		2.5
	ACGIH TLV	STEL		2.5

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses with side shields, chemical resistant goggles, or face shield. Contact lenses should not be worn.

**SKIN:** Permeation resistant gloves (butyl rubber, nitrile rubber or poly vinyl alcohol). Please note that PVA degrades in water. Cover exposed skin as possible with appropriate clothing. If skin creams are used, keep area covered by cream to a minimum.

**RESPIRATORY:** No special requirements under ordinary conditions of use and with adequate ventilation. Use NIOSH approved mist respirator where spray occurs.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** No appreciable odor.

**ODOR THRESHOLD:** Not Available

**APPEARANCE:** Powder

**COLOR:** White

**pH:** 10.5 to 11

**PERCENT VOLATILE:** NA = Not Applicable

**FLASH POINT AND METHOD:** NA = Not Applicable

**FLAMMABLE LIMITS:** 0 to 0

**AUTOIGNITION TEMPERATURE:** NA = Not Applicable

**VAPOR PRESSURE:** Vapor is water

**VAPOR DENSITY:** Same as water vapor.

**SPECIFIC GRAVITY:** 2.26

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** Stable under normal conditions of use and storage.

**INCOMPATIBLE MATERIALS:** Avoid contact with acids, and acid vapors.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

**DERMAL LD<sub>50</sub>:** No data available.

**ORAL LD<sub>50</sub>:** No data available.

**INHALATION LC<sub>50</sub>:** No data available.

**SERIOUS EYE DAMAGE/IRRITATION:** Eye, Skin and Inhalation Irritant.

**GERM CELL MUTAGENICITY:** Not Available

**REPRODUCTIVE TOXICITY:** Not Available

**STOT-REPEATED EXPOSURE:** Causes damage to lungs or kidneys through prolonged exposure via inhalation.

## 12. ECOLOGICAL INFORMATION

**AQUATIC TOXICITY (ACUTE):** Sodium Silicate has low toxicity. TLM 96 hr in mosquitofish is 2,320 mg/L.

High pH (alkalinity) of undiluted material is harmful to aquatic life.

**96-HOUR LC<sub>50</sub>:** ≤ 5000

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated

**TECHNICAL NAME:** NA = Not Applicable

**PRIMARY HAZARD CLASS/DIVISION:** Not Regulated

### ROAD AND RAIL (ADR/RID)

**PROPER SHIPPING NAME:** Not Regulated

### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Not Regulated

### CANADA TRANSPORT OF DANGEROUS GOODS

**SHIPPING NAME:** Not Regulated

## 15. REGULATORY INFORMATION

**UNITED STATES**

**DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** Chronic. Irritant.**313 REPORTABLE INGREDIENTS:** There are no listed chemicals above detection limits in this compound.**TITLE III NOTES:** None above detection limits.**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** None**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
zircon (zr(sio4))	14940-68-2
Sodium Fluorosilicate	16893-85-9

**TSCA STATUS:** Components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substances Inventory.**CANADA****WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

**WHMIS CLASS:** Class D, Division 2, Subdivision A: Materials cause other toxic effects, very toxic material.**DOMESTIC SUBSTANCE LIST (INVENTORY):** Components included on inventory**16. OTHER INFORMATION****PREPARED BY:** John A Kozak    **Date Revised:** 07/08/2021**REVISION SUMMARY:** This SDS replaces the 05/12/2021 SDS.

**HMIS RATING**

<b>HEALTH</b>	*	<b>1</b>
<b>FLAMMABILITY</b>		<b>0</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>E</b>