

## SAFETY DATA SHEET



## 54 Acidproof Concrete Guniting Grade, Liquid

Date Issued : 12/08/2015

SDS No : SCC-054GUNL

Date Revised : 02/11/2020

Revision No : 2

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 54 Acidproof Concrete Guniting Grade, Liquid**PRODUCT DESCRIPTION:** Acidproof Cement, Liquid**PRODUCT CODE:** 54GUNL**CHEMICAL FAMILY:** Potassium Silicate Solution**MANUFACTURER**

Sauereisen  
160 Gamma Drive  
Pittsburgh, PA 15238

**Emergency Contact:** John Kozak**Emergency Phone:** (800)444-8235**Alternate Contact:** Don Schubert**Customer Service:** 412 963-0303**E-Mail:** jakozak@sauereisen.com**24 HR. EMERGENCY TELEPHONE NUMBERS**

Poison Control Center (Medical):1-800-222-1222

CHEMTREC (US Transportation): 1-800-424-9300

CHEMTREC (Canada Transportation):1-703-527-3887

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Respiratory Tract Irritation, Category 3

Skin Irritation, Category 2

Eye Irritation, Category 2B

**GHS LABEL**

Exclamation  
mark

**SIGNAL WORD:** WARNING**HAZARD STATEMENTS**

H320: Causes eye irritation.

H315: Causes skin irritation.

H335: May cause respiratory irritation.

**PRECAUTIONARY STATEMENTS****Prevention:**

P264: Wash ... thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

**Response:**

P302+P352: IF ON SKIN: Wash with plenty of water/...

P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

**Disposal:**

P501: Dispose of contents/container in accordance with local/national regulations.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Contact causes eye irritation.

**SKIN:** Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

**INHALATION:** Causes sneezing and burning or itching in nose and throat.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt.%	CAS
silicic acid, potassium salt	< 45	1312-76-1
Water	> 55	7732-18-5

**4. FIRST AID MEASURES**

**EYES:** Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

**SKIN:** Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

**INGESTION:** If Swallowed, do not induce vomiting. Immediately drink two large glasses of water or activated charcoal slurry. Seek Medical attention. Never give anything by mouth to an unconscious person.

**INHALATION:** Not expected to be a problem.

**ADDITIONAL INFORMATION:** Note: To prepare activated charcoal slurry, add 50 grams of activated charcoal to 400 ml of water and mix well.

**5. FIRE FIGHTING MEASURES**

**FLAMMABLE CLASS:** NA = Not Applicable

**EXPLOSION HAZARDS:** NA = Not Applicable

**FIRE FIGHTING PROCEDURES:** NA = Not Applicable

**FIRE EXPLOSION:** NA = Not Applicable

**SENSITIVE TO STATIC DISCHARGE:** None

**SENSITIVITY TO IMPACT:** None

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

**LARGE SPILL:** For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing.

For Industrial Use only!

Do not take internally.

May cause irritation.

Wear chemical splash goggles, gloves and protective clothing.

Wash thoroughly after handling.

**STORAGE:** Store in a cool, dry place.

Keep container closed when not in use.

Keep away from food and drinking water.

Always mix well before using.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Normal ventilation for good working conditions should be used.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Chemical resistant goggles and/or face shield.

**SKIN:** Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved workclothes. Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

**RESPIRATORY:** Use NIOSH approved mist respirator where spray occurs. For emergencies, a self contained breathing apparatus or a full-face respirator is recommended. If TLV of any component is exceeded, use appropriate respiratory protection or ventilate in accordance with OSHA Regulation 29 CFR 1910.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** No appreciable odor.

**ODOR THRESHOLD:** NA = Not Applicable

**APPEARANCE:** Liquid

**COLOR:** Hazy to clear

**pH:** 11 to 12

**PERCENT VOLATILE:** NA = Not Applicable

**FLASH POINT AND METHOD:** NA = Not Applicable

**FLAMMABLE LIMITS:** 0 to 0

**VAPOR PRESSURE:** Vapor is water

**VAPOR DENSITY:** Same as water vapor.

**BOILING POINT:** (212°F)

**FREEZING POINT:** (32°F)

**MELTING POINT:** (32°F)

**SOLUBILITY IN WATER:** 100 %

**EVAPORATION RATE:** < 1

**SPECIFIC GRAVITY:** 1.26 to 1.39

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** Stable under normal conditions of use and storage.

**CONDITIONS TO AVOID:** Flammable hydrogen gas may be produced on prolonged contact with metals such as Aluminum, tin, lead, and zinc.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.

**INCOMPATIBLE MATERIALS:** Materials to avoid: Acids, salts, or alcohols may cause gel formation (non-hazardous).

## 11. TOXICOLOGICAL INFORMATION

**SERIOUS EYE DAMAGE/IRRITATION:** Eye, Skin and Inhalation Irritant.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** No data available. Contact Env. Dept.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

**EMPTY CONTAINER:** Disposal must be made according to official regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated

**TECHNICAL NAME:** NA = Not Applicable

**PRIMARY HAZARD CLASS/DIVISION:** Not Regulated

### 15. REGULATORY INFORMATION

#### UNITED STATES

#### DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7/8: Keep container tightly closed and dry.

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Irritant.

**313 REPORTABLE INGREDIENTS:** There are no listed chemicals above detection limits in this compound.

**TITLE III NOTES:** None above detection limits.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
silicic acid, potassium salt	1312-76-1
Water	7732-18-5

**CALIFORNIA PROPOSITION 65:** Known to the State of California to cause cancer or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

#### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7/8: Keep container tightly closed and dry.

**WHMIS CLASS:** Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** Components included on inventory

### 16. OTHER INFORMATION

**PREPARED BY:** John Kozak    **Date Revised:** 02/11/2020

**REVISION SUMMARY:** This SDS replaces the 12/14/2018 SDS.

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>2</b>
<b>FLAMMABILITY</b>		<b>0</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>