

SAFETY DATA SHEET

Proprietary SDS.

Date Prepared : 12/3/2014
SDS No : SCC-0DW30

DW-30 Electrical Cement, Powder

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DW-30 Electrical Cement, Powder
PRODUCT DESCRIPTION: Electrical Cement, Powder
PRODUCT CODE: DW30
PRODUCT FORMULATION NAME: DW-30 Electrical Cement, Powder
CHEMICAL FAMILY: Magnesium Oxide Cement

MANUFACTURER

Sauereisen
 160 Gamma Drive
 Pittsburgh, PA 15238

Emergency Contact: Greg Maloney**Emergency Phone:** 412-963-0303**Alternate Emergency Phone:** 412-963-0303**Customer Service:** x244**E-Mail:** gdmaloney@sauereisen.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical) : (877) 800-5553**CANUTEC (Canadian Transportation) :** (613) 996-6666**CHEMTREC (US Transportation) :** (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 4
 Eye Irritation, Category 2B
 Skin Irritation, Category 2
 Target Organ Toxicity (Repeated exposure), Category 2
 Carcinogenicity, Category 1B

GHS LABEL



Exclamation
mark



Health
hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H315: Causes skin irritation.
 H320: Causes eye irritation.
 H333: May be harmful if inhaled.
 8576ZUY1: May cause cancer.
 8492XP4O: May cause damage to Lungs or Kidneys through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.
 P314: Get medical advice/attention if you feel unwell.
 P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing and wash before reuse.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P405: Store locked up.

Disposal:

58525E4V: Dispose of contents/container to in accordance with local/national regulations

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

INHALATION: Dust or vapor irritating to eyes and respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Magnesium Oxide	< 30	1309-48-4
Silica, Crystalline	< 30	14808-60-7
Sulfuric Acid, Magnesium Salt (1:1)	< 30	7487-88-9

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

INGESTION: If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention immediately. Never give anything by mouth to an unconscious person. Advise physician of possible fluoride exposure.

INHALATION: If difficulty breathing, move to fresh air once. Apply artificial respiration if breathing has stopped. Seek medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes pain, redness and tearing.

SKIN: Contact causes skin irritation.

INHALATION: Headache, nausea, and irritation to nose and throat. Prolonged or repeated exposure may cause asthma.

CHRONIC EFFECTS: The adverse health effects-- silicosis, lung cancer, autoimmune and chronic kidney diseases, tuberculosis and non-malignant respiratory diseases-- are chronic effects.

Prolonged exposure to fluoride over years may produce an embrittlement and densification of bones and increase calcification of ligaments.

NOTES TO PHYSICIAN: Further treatment may be necessary. Contact local poison control center. Rinse mouth.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: NA = Not Applicable

FLAME PROPAGATION OR BURNING RATE OF SOLIDS: None

GENERAL HAZARD: NA = Not Applicable

EXTINGUISHING MEDIA: NA = Not Applicable

HAZARDOUS COMBUSTION PRODUCTS: NA = Not Applicable

EXPLOSION HAZARDS: Not sensitive to mechanical impact or static discharge

FIRE FIGHTING PROCEDURES: NA = Not Applicable

FIRE FIGHTING EQUIPMENT: NA = Not Applicable

FIRE EXPLOSION: NA = Not Applicable

SENSITIVE TO STATIC DISCHARGE: None

SENSITIVITY TO IMPACT: None

HAZARDOUS DECOMPOSITION PRODUCTS: NA = Not Applicable

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

LARGE SPILL: For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

SPECIAL PROTECTIVE EQUIPMENT: Wear gloves, rubber boots, and safety glasses.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin, and clothing.

For industrial use only!

Do not take internally.

May cause irritation.

Wash thoroughly after handling.

HANDLING: Wear protective safety glasses, gloves and protective clothing.

STORAGE: Store in a cool, dry place.

Keep container closed when not in use.

Keep away from food and drinking water.

Always mix well before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Magnesium Oxide	TWA		15		10 I		
Silica, Crystalline	TWA		10		0.025	NL	NL
	STEL	0.1				NL	NL

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses with side shields, chemical resistant goggles, or face shield. Contact lenses should not be worn.

SKIN: Permeation resistant gloves (butyl rubber, nitrile rubber or poly vinyl alcohol). Please note that PVA degrades in water. Cover exposed skin as possible with appropriate clothing. If skin creams are used, keep area covered by cream to a minimum.

RESPIRATORY: This product contains encapsulated silica. By OSHA letter of interpretation, the silica is not considered respirable in either the cement paste form, or cured cement form. However, if the cured cement is polished, ground, or chipped during processing, handling, or use, the silica may be released as an airborne respirable particle. In these Instances appropriate personal protective equipment and local ventilation controls must be employed.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: No appreciable odor.

ODOR THRESHOLD: Not Available

APPEARANCE: Powder

COLOR: White to tan.

pH: 10

PERCENT VOLATILE: NA = Not Applicable

FLASH POINT AND METHOD: NA = Not Applicable

FLAMMABLE LIMITS: NA to NA

AUTOIGNITION TEMPERATURE: NA = Not Applicable

VAPOR PRESSURE: NA = Not Applicable

VAPOR DENSITY: NA = Not Applicable

BOILING POINT: (4046°F)

MELTING POINT: (3110°F)

SPECIFIC GRAVITY: 1

(VOC): 115.000

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under normal conditions of use and storage.

HAZARDOUS DECOMPOSITION PRODUCTS: Silica will dissolve in hydrofluoric acid and produce a corrosive gas - Silicon tetrafluoride.

INCOMPATIBLE MATERIALS: Avoid contact with acids, and acid vapors.

11. TOXICOLOGICAL INFORMATION

ACUTE

DERMAL LD₅₀: No data available.

ORAL LD₅₀: No data available.

INHALATION LC₅₀: No data available.

EYE EFFECTS: Irritant.

SKIN EFFECTS: Irritant.

CHRONIC: The adverse health effects -- silicosis, lung cancer, autoimmune and chronic kidney diseases, tuberculosis, and non-malignant respiratory diseases -- are chronic effects.

CARCINOGENICITY

IARC: Silica is listed as having sufficient evidence to be a carcinogen in humans and in experimental animals, for the carcinogenicity of quartz and cristobalite. The overall IARC evaluation was that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1).

NTP: The National Toxicology Program, in its Ninth Annual report on Carcinogens, classified "silica, crystalline (respirable)" as a known human carcinogen.

OSHA: Crystalline Silica (Quartz) is not regulated by the US Occupational Safety and Health Administration as a carcinogen.

Notes:

Silica is listed by IARC and NTP as having sufficient evidence to be a carcinogen in humans and in experimental animals for the carcinogenicity of quartz and cristobalite. The overall IARC evaluation was that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1).

IRRITATION: Eye, Skin and Inhalation Irritant.

NEUROTOXICITY: Not Available

REPRODUCTIVE EFFECTS: Not Available

TARGET ORGANS:

·Nephrotoxicity - Recent studies suggest that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of kidney disorders.

TERATOGENIC EFFECTS: Not Available

MUTAGENICITY: Not Available

SYNERGISTIC MATERIALS: Not Available

GENERAL COMMENTS:

ADDITIONAL INFORMATION: Crystalline Silica (Quartz)

·Silicosis - The major concern is silicosis caused by the inhalation of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute.

·Scleroderma - There is evidence that exposure to respirable crystalline silica or silicosis is associated with incidence of scleroderma of the lungs.

·Tuberculosis - Individuals with silicosis are at risk to develop tuberculosis, if exposed to persons with tuberculosis.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Crystalline silica (quartz) is not known to be an environmental hazard.

AQUATIC TOXICITY (ACUTE): Sodium Silicate has low toxicity. TLM 96 hr in mosquitofish is 2,320 mg/L.

High pH (alkalinity) of undiluted material is harmful to aquatic life.

96-HOUR LC₅₀: ≤ 5000

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated

TECHNICAL NAME: NA = Not Applicable

PRIMARY HAZARD CLASS/DIVISION: Not Regulated

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not Regulated

AIR (ICAO/IATA)

SHIPPING NAME: Not Regulated

VESSEL (IMO/IMDG)

SHIPPING NAME: Not Regulated

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Chronic. Carcinogen. Irritant.

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** No **CHRONIC:** No

313 REPORTABLE INGREDIENTS: There are no listed chemicals above detection limits in this compound.

TITLE III NOTES: None above detection limits.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Magnesium Oxide	1309-48-4
Silica, Crystalline	14808-60-7
Sulfuric Acid, Magnesium Salt (1:1)	7487-88-9

TSCA STATUS: Components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

REGULATIONS

STATE REGULATIONS:

Massachusetts Toxic Use Reduction Act- Silica, Crystalline (respirable size, <10microns) is toxic for purposes of the Massachusetts Toxic Use Reduction Act

Pennsylvania Worker and Community Right to Know Act- Quartz is a hazardous substance under the act, but it is not a special hazardous substance or an environmental hazardous substance.

California Inhalation Reference Exposure Level (REL)- California established a chronic REL of 3 ug for silica crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

CALIFORNIA PROPOSITION 65: Known to the State of California to cause cancer and reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

S22: Do not breathe dust.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

WHMIS CLASS: Class D, Division 2, Subdivision A: Materials cause other toxic effects, very toxic material.

DOMESTIC SUBSTANCE LIST (INVENTORY): Components included on inventory

16. OTHER INFORMATION

PREPARED BY: John A Kozak **Date Prepared:** 12/3/2014

HMIS RATING

HEALTH	*	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		E