

SAFETY DATA SHEET



F88 Chimney Seal, Part B, Urethane Membrane

Date issued : 05/18/2015
 SDS number : SCC-F88B
 Date revised : 05/29/2024
 Revision number : 2

1. Identification

Product code: F88GB

Product identifier: F88 Chimney Seal, Part B, Urethane Membrane

Chemical family: Urethane

Manufacturer / Supplier

Sauereisen
 160 Gamma Drive
 Pittsburgh, PA 15238

Emergency contact: John Kozak

Emergency Phone: (800)444-8235

Alternate Contact: Pete Jansen

Customer Service: 412 963-0303

E-Mail: jakozak@sauereisen.com

Emergency telephone number (24 hour)

Poison Control Center (Medical): 1-800-222-1222

CHEMTREC (US Transportation): 1-800-424-9300

CHEMTREC (Canada Transportation): 1-703-527-3887

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Acute Toxicity (Oral), Category 4
 Eye Irritation, Category 2B
 Skin Irritation, Category 2
 Respiratory Tract Irritation, Category 3
 Acute Toxicity (Dermal), Category 5

Label elements



Exclamation
 mark

Signal word: WARNING

Hazard statement(s)

H315: Causes skin irritation.
 H227: Combustible liquid.
 H320: Causes eye irritation.
 H302: Harmful if swallowed.
 H335: May cause respiratory irritation.
 H313: May be harmful in contact with skin.

Precautionary statement(s)

Prevention:

P264: Wash ... thoroughly after handling.
 P270: Do not eat, drink or smoke when using this product.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.

P330: Rinse mouth.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P321: Specific treatment (see ... on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/national regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
asphalt (cutback)	< 15	8052-42-4
Distillates, Petroleum, Hydrotreated Heavy Naphthenic	< 20	64742-52-5
1,3 butadiene, homopolymer, hydroxy-terminated	< 60	69102-90-5

4. First-aid measures

Eye: Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

Skin: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

Ingestion: If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention immediately. Never give anything by mouth to an unconscious person.

Inhalation: If difficulty breathing, move to fresh air once. For acute overexposure, give oxygen if breathing is difficult. Apply artificial respiration if breathing has stopped. Keep patient warm and at rest. Seek immediate medical attention.

Most important symptoms and effects, both acute and delayed

Eye: Can cause redness, tearing, Irritation, inflammation and corneal opacity.

Skin: Moderate irritation and dryness. Prolonged or repeated exposure may result in sensitization.

Inhalation: Inhalation may cause dizziness, stupor, unconsciousness, central nervous system depression, weakness, vomiting, drowsiness, blurred vision, headache and nausea.

Chronic effects: Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response. Ingestion may cause bleeding of the gastrointestinal tract and the vomiting of blood.

5. Fire-fighting measures

Suitable extinguishing media: Do not use water, which may spread fire. Extinguish with foam, dry chemical, carbon dioxide, earth or sand.

Hazardous combustion products: Combustion products may be toxic.

Explosion hazards: Not sensitive to mechanical impact or static discharge

Fire fighting procedures: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

Fire fighting equipment: Toxic fumes will be evolved when this material is involved in a fire. Self-contained breathing apparatus should be available for fire fighters.

Fire explosion: Sudden reaction and fire may result if this product is mixed with an oxidizing agent. Cool fire exposed containers with water.

Sensitivity to static discharge: None

Sensitivity to mechanical impact: None

6. Accidental release measures

Small spill: Absorb with non-combustible, granular material (e.g. sand) Remove by mechanical means and place material in covered container temporarily for later disposal.

Large spill: Evacuate area. Turn off ignition sources. Stop leak, if possible without risk. Wear self-contained breathing apparatus and full protective clothing during clean up. Dike spill and pump into salvage tank. Absorb remaining liquid with sand or other non-combustible, granular material. Remove by mechanical means.

7. Handling and storage

General procedures:

Avoid contact with eyes, skin, and clothing.

For industrial use only! Do not take internally.

May cause irritation.

Do not eat, drink or smoke when using this product.

Wear chemical splash goggles, gloves and protective clothing.

Avoid high ambient temperatures and humidity.

Wash thoroughly after handling.

Conditions for safe storage:

Store in a cool, dry place.

Keep container closed when not in use.

Store away from direct heat and flame.

Keep away from food and drinking water.

Store out of direct sunlight.

DO NOT SMOKE where product is used or stored.

Store in a well-ventilated place.

Always mix well before using.

Store away from combustible and incompatible materials.

Ground containers when transferring materials.

Remove all sources of ignition or sparks from area.

Empty containers may have residue and flammable vapors. Do not expose to heat, cut, weld, or puncture empty container

8. Exposure controls/personal protection

Exposure controls

Control parameters			
Chemical name	Occupational exposure limit values		
	Type	ppm	mg/m ³
asphalt (cutback)	ACGIH TLV	TWA	5
Distillates, Petroleum, Hydrotreated Heavy Naphthenic	OSHA PEL	STEL	5
	ACGIH TLV	TWA	5
	Supplier OEL	TWA	NL
		STEL	NL

Appropriate engineering controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection: Chemical resistant goggles and/or face shield.

Skin protection - hand protection: Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved workclothes. Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

Respiratory protection: Use organic vapor cartridges in respirators. If TLV of any component is exceeded use appropriate

respiratory protection or ventilate in accordance with OSHA Regulation 29 CFR Part 1910.V.

Skin protection - other: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

Occupational hygiene practices: Wash thoroughly after handling. Safety shower and eyewash station should be within direct access. Keep containers closed.

9. Physical and chemical properties

Appearance: Liquid

Color: Black

Odor: Characteristic Asphalt odor

pH: NA = Not Applicable

Initial boiling point and boiling range: > (350°F)

Flash point: (325°F)

Lower explosion limit / flammability limit: NE

Upper explosion limit / flammability limit: NE

Relative density: 1

Solubility: Insoluble

Auto-ignition temperature: Not Established

Percent volatiles: 0

10. Stability and reactivity

Reactivity: Yes

Dangerous polymerization: None

Chemical stability: Stable under normal conditions of use and storage.

Conditions to avoid: Avoid excessive heat and flame. May react with strong oxidants such as chlorates, bromides, and nitrates.

Hazardous decomposition products: Thermal decomposition or burning may produce toxic compounds such as carbon monoxide, carbon dioxide, sulfur oxides, various complex organic compounds

Incompatible materials: Materials to avoid: Strong oxidants such as liquid chlorine, pure oxygen, or calcium hypochloride.

11. Toxicological information

Acute toxicity

Acute dermal toxicity LD₅₀: > 2000 mg/kg (rabbit)

Acute oral toxicity LD₅₀: 2000 mg/kg (rat)

Acute inhalation toxicity LC₅₀: Not Available

Serious eye damage / irritation: Eye, Skin and Inhalation Irritant.

Respiratory or skin sensitization: Skin and Respiratory sensitizer.

Germ cell mutagenicity: No Data Available

Specific Target Organ Toxicity - single exposure: May cause Liver or Kidney damage, may affect the blood or blood-forming organs.

12. Ecological information

Aquatic toxicity, both acute and chronic: TLM 96 > 1000 ppm

Environmental data: May be dangerous if it enters water intakes. Notify Local health and Pollution control officials. Notify operators of nearby water intakes.

Asphalt can have disastrous effects on bottom life.

13. Disposal considerations

Disposal methods: The packaging and material may be disposed of in landfills; however, material should be covered or wetted to minimize generation of airborne dust.

Empty container: Disposal must be made according to official regulations.

RCRA/EPA waste information: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR 261 et seq.

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: Not Regulated

UN number: NA

Transport hazard class(es): Not Regulated

Packing group, if applicable: NA

Hazard label: NA = Not Applicable

ADR / RID - road / rail

UN proper shipping name: Not Regulated

UN number: NA

Hazard class: Not Regulated

Packing group, if applicable: NA

Hazard label: None

ICAO / IATA - air

UN proper shipping name: Not Regulated

Technical name: NA = Not Applicable

UN number: NA

Transport hazard class(es): Not Regulated

Packing group, if applicable: NA

IMO / IMDG - International

UN proper shipping name: Not Regulated

Technical name: NA = Not Applicable

UN number: NA

Transport hazard class(es): Not Regulated

Packing group, if applicable: NA

Canadian Transport of Dangerous Goods Regulations (TDG)

UN proper shipping name: Not Regulated

UN number: NA

Transport hazard class(es): Not Regulated

Packing group, if applicable: NA

Hazard label: None

15. Regulatory information

UNITED STATES

Dot label symbol and hazard classification

R18: In use, may form flammable/explosive vapour-air mixture.

R21/22: Harmful in contact with skin and if swallowed.

S20/21: When using do not eat, drink or smoke.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S7/8: Keep container tightly closed and dry.

S7/9: Keep container tightly closed and in a well-ventilated place.

SARA Section 311/312 Hazard Categories

311/312 Health hazards: Chronic. Fire Hazard. Irritant.

313 reportable ingredients: There are no listed chemicals above detection limits in this compound.

Title III notes: None above detection limits.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

CERCLA regulatory: Crystalline silica (Quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), 40 CFR 302

TSCA (The Toxic Substances Control Act)

Chemical name	CAS No.
asphalt (cutback)	8052-42-4
Distillates, Petroleum, Hydrotreated Heavy Naphthenic	64742-52-5

TSCA Status: Components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

Regulations

State regulations:

Massachusetts Toxic Use Reduction Act- Silica, Crystalline (respirable size, <10 microns) is toxic for purposes of the Massachusetts Toxic Use Reduction Act

Pennsylvania Worker and Community Right to Know Act- Quartz is a hazardous substance under the act, but it is not a special hazardous substance or an environmental hazardous substance.

California Inhalation Reference Exposure Level (REL)- California established a chronic REL of 3 ug for silica crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

California Proposition 65: Known to the State of California to cause cancer or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.

RCRA status: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR 261 et seq.

CANADA

WHMIS Hazard Symbol and Classification



Toxic



Combustible
Liquid

R18: In use, may form flammable/explosive vapour-air mixture.

R21/22: Harmful in contact with skin and if swallowed.

S20/21: When using do not eat, drink or smoke.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S7/8: Keep container tightly closed and dry.

S7/9: Keep container tightly closed and in a well-ventilated place.

WHMIS Classification: Class B, Division 2, Flammable Liquid.

Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL): Components included on inventory

16. Other information

Revision summary: This SDS replaces the 06/17/2020 SDS. Revised: **Section 2:** Classification of the substance or mixture, Label elements, Precautionary statement(s).

HMIS rating

HMIS rating	
Health	<input type="checkbox"/> 1
Flammability	<input type="checkbox"/> 1
Physical hazard	<input type="checkbox"/> 0
Personal protection	<input type="checkbox"/> H